

## VERIFICATION OF COMPLIANCE


No.: GZES2306010331PV

Applicant: Global Tech China Ltd.  
Unit 702-704, 7/F., Texwood Plaza, 6 How Ming Street, Kwun Tong, Kln.,  
Hong Kong, China

Manufacturer: Global Tech China Ltd.  
Unit 702-704, 7/F., Texwood Plaza, 6 How Ming Street, Kwun Tong, Kln.,  
Hong Kong, China

Product Name: Hybrid Inverter

Model No.: SM3.6kWPL, SM2.5kWPL, SM3.6kWLS, SM2.5kWLS, SM3.6kWLL,  
SM2.5kWLL, LIFE3.6HYB02, LIFE2.5HYB02

Trade Mark: 

Rating: Refer to page 2

Protection against Electric Shock: Class I

Degree of Protection: IP 20

Additional Information (if any): **Master Software version:** VER1.5(LCD MCU & DSP), VER1.0(Slave MCU)

Sufficient samples of the product have been tested and found to be in conformity with

Test Standard: VDE 0126-1-1: 2013

as shown in the GZES230601033101

Test Report Number(s):

This Verification of GPSD Compliance has been granted to the applicant based on the results of tests performed by Laboratory of SGS-CSTC Standards Technical Services Co., Ltd. on sample of the above-mentioned product in accordance with the provisions of the relevant specific standards and the General Product Safety Directive 2001/95/EC.

  
David Guo

Senior Technical Manager

SGS-CSTC

2023-07-13

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services which can be accessible at <https://www.sgs.com/en/terms-and-conditions>

Member of SGS Group (Société Générale de Surveillance)

No.:

GZES2306010331PV

Other information added:

Rating:

Model	SM3.6kWPL, SM3.6kWLS, SM3.6kWLL, LIFE3.6HYB02,	SM2.5kWPL, SM2.5kWLS, SM2.5kWLL, LIFE2.5HYB02
PV Input data		
Max. PV Input Voltage	500V	
Max. PV current	12 d.c.A	12 d.c.A
Max. PV Isc	12.7 d.c.A	12.7 d.c.A
AC output/Input data		
Nominal input / output power	3600W	2500W
Max. apparent power	3960VA	2500VA
Nominal voltage	230 a.c.V	
Max. input/output current	16 a.c.A	11 a.c.A
Nominal Frequency	50 Hz	
Power Factor range	0.8 Leading ~ 0.8 Lagging	
Stand alone data		
Nominal output power	3600W	2500W
Nominal AC output voltage	230 a.c.V	
Nominal AC Frequency	50Hz	
Battery data		
Battery voltage range	40 – 58 d.c.V	
Max. charging and discharging current	60/80 d.c.A	42/56 d.c.A
Type of battery	LiFePO4	
Ingress Protection	IP20	
Protective Class	Class I	
Operating temperature range	-25°C - +60°C (>45°C derating)	
Firmware version	VER1.5(LCD MCU & DSP), VER1.0(Slave MCU)	

David Guo

Senior Technical Manager  
SGS-CSTC

2023-07-13

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services which can be accessible at <https://www.sgs.com/en/terms-and-conditions>

Member of SGS Group (Société Générale de Surveillance)